

WISI DL 100

Surge protector



Description

Overvoltage protection for coaxial connections, especially for satellite signal distributions, multiswitches and headend systems. With the DL100, all following components are protected from undesirable voltage peaks.

At a glance:

- Over voltage protection for satellite signal distribution systems
- Overvoltage protection for headends
- Suitable for wideband applications up to 2.4 GHz
- Inline design for easy installation
- Typical application between LNB and multiswitches / headends
- DC loop through

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-0, Fax - 350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 26. März 2025, 11:37 AM

Technical data

Connectors

Input	F-socket / 75 Ohm
Output	F-plug / 75 Ohm
Frequency range	5 ... 2.400
Through loss	0.8 ... 1.2
Return loss	>10 dB
Rated leakage current (8/20 µs)	8 kA
Breakdown voltage 100V/s	230V +/- 42V
Operating voltage	max. 25V
Operating current	max. 1A

General Data

Dimensions (width x height x depth)	diameter 14 mm / length 48 mm
Weight	0.025 kg
Screening	Class A, according to EN 50083-2

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	14 x 14 x 48 mm
Packaging volume sales unit	0.01 dm ³
Gross weight sales unit	0.025 kg
EAN	4010056740269
Article number	74026
Customs tariff number	85363010