

# WISI DS 35 0035

DATA-connection cable F-Quick + F-Quick, 0,35 m



## Description

The DS 35 0035 is a data connection cable. It is provided with two F-Quick plug. The outer sheath material is made of PVC and the length of the cable is 0.35 m long.

### At a glance:

- 2x F-Quick straight
- 0,35 m length
- Ideal patch cable with flexible outer sheath

#### WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7  
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350  
E-Mail: [export@wisi.de](mailto:export@wisi.de)

Technical Modifications reserved. WISI cannot be held liable for any printing error. 18. November 2020, 9:27 vorm.

## Technical data

### Mechanical Data

|                       |                          |
|-----------------------|--------------------------|
| Length                | 0,35 m                   |
| Outer jacket material | PVC RoHS compliant white |
| Outer jacket diameter | Ø5,0 mm                  |

### Cable construction

|                              |                          |
|------------------------------|--------------------------|
| Inner conductor material     | Cu                       |
| Inner conductor diameter     | Ø0,8 mm                  |
| Dielectric                   | Zell-PE, physics. foamed |
| Dielectricum diameter        | Ø3,55 mm                 |
| Outer conductor 1            | AL/Pet bonded            |
| Outer conductor 2            | CuSn                     |
| Outer conductor 3            | AL/Pet                   |
| F-quick-male outer conductor | nickel plated brass      |
| F-quick-male inner conductor |                          |

### Electrical data

|                                |                                  |
|--------------------------------|----------------------------------|
| Frequency range                | 5...1000 MHz                     |
| Through loss                   | <1 dB                            |
| Return loss                    | <20 dB                           |
| Coupling resistance 5...30 MHz | 5 mΩ/m                           |
| Screen class 30 ... 1000 MHz   | 85 dB                            |
| Screening factor               | Class A, according to EN 50083-2 |

## Packaging data

|                                   |                    |
|-----------------------------------|--------------------|
| Sales unit                        | 1 pcs.             |
| Dimensions (WxHxD) sales unit     | 570 x 370 x 160 mm |
| Packaging volume sales unit       | dm³                |
| Gross weight sales unit           | 0.024 kg           |
| Shipping unit                     | pcs.               |
| Dimensions (WxHxD) shipping unit  | mm                 |
| Packaging volume shipping package | 0.136 dm³          |
| Gross weight shipping unit        | 0.024 kg           |
| EAN                               | 4010056720674      |
| Article number                    | 72067              |
| Customs tariff number             | 85444210           |