

Description

Triple shielded coaxial cable for Broadband Distribution Networks
75 Ohm
Triple shielded cable (Screening Class A)

**Data Sheet****TS703J**

Ø	1,13	4,80	4,97	5,37	5,49	6,90
	(Cu)	(PEG)	(Al/Pet/Al/Sur)	(CuSn)	(AL/Pet J-foil)	(PVC)

Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/ 2011 for the class of performance specified on the related product label.

Standards

EN 50117-2-4

Reaction to Fire

EN50575

Application

DOCSIS 3.1 (Data Over Coax System)

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,13 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,80 ± 0,10	mm
Aluminium/Polyester/Aluminium/Surlyne tape longitudinally overlapped and bonded to the dielectric	(Al/Pet/Al/Sur)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		45	%
Outer Aluminium/Polyester j-folded and longitudinally overlapped	(Al/Pet J-foil)	21,5+3,5 x 30/19	mm/µm
Diameter over Braid		Ø 5,49	mm
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 6,90 ± 0,20	mm

Printed each meter by blue ink-jet :

CAVEL TS 703 J MADE IN ITALY 75 Ohm Euroclass Eca EN50117-2-4 Class A CEI-UNEL 36762 C-4 (U0 = 400V) ULTRA HD / 4K gggaa(n) m

(gggaan=batch)

Physical data

Weight of copper conductors	14,62	kg/km
Total weight of cable	43,87	kg/km
Minimum bending radius (single/repeated bending)	35/70	mm
Maximum cable pulling strength	150	N
Stripping force between braid and sheath over 200 mm	> 130	N
Minimum installation temperature	-5	°C
Operating temperature	-40 / +80	°C

Electrical data

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date**29/02/2016****Responsible****PierPaolo Piccinini**

Description

Triple shielded coaxial cable for Broadband Distribution Networks
 75 Ohm
 Triple shielded cable (Screening Class A)

**Data Sheet****TS703J**

Inner conductor resistance	18	Ohm/km
Outer conductor resistance	14	Ohm/km
Loop resistance	32	Ohm/km
Sheat Insulation voltage (spark test)	3	kV
Maximum current (I _{eff})	8	A
Structural return loss (SRL)		
5 - 470 MHz	>30 dB	
470 - 1000 MHz	>28 dB	
1000 - 2000 MHz	>26 dB	
2000 - 3000 MHz	>22 dB	
Screening Attenuation (SA)	SA-Class A++	Shield Transfer Impedance (Zt)
30 - 1000 MHz	>105 dB	5 - 30 MHz
1000 - 2000 MHz	>100 dB	
2000 - 3000 MHz	>85 dB	
		Zt-Class A
		< 4,5 mOhm/m

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,60	862	17,20
10	2,30	1000	18,60
30	3,20	1750	25,20
50	4,10	2150	28,10
200	8,00	2400	29,70
300	9,80	3000	33,70
470	12,50		

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date**29/02/2016****Responsible****PierPaolo Piccinini**

Description

Triple shielded coaxial cable for Broadband Distribution Networks
75 Ohm
Triple shielded cable (Screening Class A)




Data Sheet

TS703J

Attenuazione di schermatura / Screening Attenuation


Cavo classe A++ / A++ Class cable

Cavo tipo / Cable type : TS703J



Transfer Impedance

Cable type: TS703J



ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

PierPaolo Piccinini

Description

Triple shielded coaxial cable for Broadband Distribution Networks
75 Ohm
Triple shielded cable (Screening Class A)

**Data Sheet****TS703J****Connectors**

BNCC703	Series BNC Compression, BNC Compression, for OUTDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm
F703	Series F Crimp, F Crimp, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
F90	Series F Crimp, F Crimp, for INDOOR installation
FA703	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
FC7.0QM	Series F Compression, Quick Mount, for OUTDOOR installation
FC703	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass - 30,0 mm x 12,0 mm
FCEM7.0C	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass
FCPO5.1C	Series F Compression, Ø 5,1 Push-On, for OUTDOOR installation, nitin-plated brass
FR703	Series F Crimp, F crimp, "Rapid", for INDOOR installation
IECF5.1C	Series IEC (toolless), female, no tool, for INDOOR installation
IECF90C	Series IEC (toolless), Ø 5,1 90° female, for INDOOR installation
IECF703	Serie IEC Compression, female, no tool, for OUTDOOR installation
IECM5.1C	Series IEC (toolless), male, no tool, for INDOOR installation
IECM90C	Series IEC (toolless), Ø 5,1 90° male, for INDOOR installation
IECM703	Serie IEC Compression, male, for OUTDOOR installation
FC703C	Series F Compression, F Compression, for OUTDOOR installation

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date**29/02/2016****Responsible****PierPaolo Piccinini**