

# WISI DM 16 B

SAT splitter, 6-way



## Description

The DM 16 B is a 6-way distributor which enables the symmetrical division of antenna signals on 6 lines. The integrated DC bypasses enable the pass-through of distributor voltage. The distribution attenuation is 17 dB. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems.

## At a glance:

- Frequency range from 5....2400 MHz
- Screening factor according to Class A
- DC-Bypass over every output
- High port isolation and return loss

## Technical data

Frequency range	5...2400 MHz
Distribution loss	11...17 dB
Isolation	>20 dB
Return loss	18 dB

## Connectors

F-socket	7 pcs. (1x input, 6x output)
----------	------------------------------

## General data

Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	92x35x28 mm

## Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	370 x 320 x 170 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.110 kg
Shipping unit	50 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.2 dm <sup>3</sup>
Gross weight shipping unit	0.11 kg
EAN	4010056165802
Article number	16580
Customs tariff number	85291095