

Description

Local Area Network Cable

Cat. 6 F/UTP 4x2xAWG23/1 LSZH


Coaxial Cables

CAVEL

since 1968

Data Sheet

LAN641ZH



Ø	0,57	1,10		7,60
	(Cu)	(PE)	(Pet) (Al/Pet)	(LSZH)

Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EIA-TIA 568-B-2	ISO/IEC 11801	IEC 61156-5	EN50173
EN50288-5-1	NF C 15-100	XP C 90-483	XP C 93-531-16

Reaction to Fire

IEC60332-1	EN50575
------------	---------

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T

IEEE 802.5; ATM

Power over Ethernet (PoE)/PoE+

Construction data

4 pairs with conductor of bare copper wires	(Cu)	Ø 0,57	mm
Dielectric of solid polyethylene	(PE)	Ø 1,10	mm
Polyester film spirally wrapped	(Pet)		

Composition

Twisted pairs, coloured by Standard TIA-568A

Drain wire of tinned copper	(CuSn)	Ø 0,40	mm
Cross separator in Polyethylene	(PE)		
External Aluminium/Polyester tape	(Al/Pet)	27 x 30/19	mm/µm
Outer sheath of Thermoplastic material - grey (RAL 7001) - halogen-free, low smoke, flame retardant and UV-resistant	(LSZH)	Ø 7,60	mm

Printed each meter by blue ink-jet :

CAVEL LAN 641 ZH MADE IN ITALY CAT 6 F/UTP 4x2xAWG23 Euroclass Eca ISO-IEC 11801 EN50173 CEI-UNEL 36762 C-4 (U0 = 400V) gggaan - m

(gggaan=batch number m=meter marking)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

06/09/2018

Responsible

Alberto Scardovi

Description

Local Area Network Cable

Cat. 6 F/UTP 4x2xAWG23/1 LSZH



Data Sheet

LAN641ZH

Physical data

Weight of copper conductors	19,92	kg/km
Total weight of cable	55,41	kg/km
Minimum bending radius x1/n	35/70	mm
Maximum cable pulling strength	100	N
Maximum tensile strength during the installation	100	N
Installation temperature	0 / +50	°C
Operating temperature	-20 / +60	°C

Electrical data

Characteristic impedance	100 MHz	100 ± 5	Ohm
Capacitance of Twisted Pair (@800Hz)		48	pF/m
Velocity Ratio		67 %	
DC Conductor Resistance		80	Ohm/km
Loop resistance		160	Ohm/km
Insulation resistance		> 5000	MOhm/km
Sheath Insulation Voltage (DC, 1 min)		1	kV
Coupling Attenuation		> 45	dB

Screening Attenuation (SA)

30 - 250 MHz	> 50 dB
250 - 1000 MHz	> 45 dB

Shield Transfer Impedance (Zt)

1 MHz	< 35 mOhm/m
10 MHz	< 41 mOhm/m
30 MHz	< 110 mOhm/m
100 MHz	< 150 mOhm/m

Transmission-Characteristic (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	SRL [dB]	NEXT [dB]	ACR [dB]	FEXT [dB]
1	1,80	25,00	100,00	98,20	90,00
10	5,40	25,00	80,00	74,60	70,00
20	7,70	25,00	70,00	62,30	60,00
31,2	9,60	25,00	65,00	55,40	53,00
62,5	13,70	25,00	60,00	46,30	50,00
100	17,40	25,00	60,00	42,60	48,00
155,5	21,90	25,00	55,00	33,10	46,00
200	25,00	20,00	55,00	30,00	44,00
250	28,10	20,00	50,00	21,90	40,00
300	30,80	20,00	45,00	14,20	

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

06/09/2018

Responsible

Alberto Scardovi