

## Description

Double shielded coaxial cable - 75 Ohm

Double shielded cable (Screening Class A+)

Coaxial Cables

CAVEL®

since 1968

Data Sheet

RP913B

Ø	1,13	4,75	4,90	5,30	6,60
	(Cu)	(PEG)	(Al/Pet)	(CuSn)	(PVC)

## Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

## Standards

EN 50117-2-4

## Reaction to Fire

IEC 60332-1-2

EN50575

## Application

DOCSIS 3.1 (Data Over Coax System)

## Construction data

Inner conductor of plain copper	(Cu)	Ø 1,13 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,75 ± 0,10	mm
Aluminium/Polyester tape longitudinally overlapped	(Al/Pet)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		72	%
Diameter over Braid		Ø 5,30	mm
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 6,60 ± 0,10	mm

Printed each meter by blue ink-jet :

**CAVEL RP 913 B MADE IN ITALY 75 Ohm Euroclass Eca EN50117-2-4 Class A+ CEI-UNEL 36762 C-4 (U0 = 400V) ULTRA HD / 4K gggaa(n) m**

(ggg=day)(aa=year)(n=batch) (m=meter marking)

## Physical data

Weight of copper conductors	19,07	kg/km
Total weight of cable	43,64	kg/km
Minimum bending radius (single/repeated bending)	35/70	mm
Maximum cable pulling strength	150	N
Minimum installation temperature	-5	°C
Operating temperature	-40 / +80	°C

## Electrical data

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		18	Ohm/km
Outer conductor resistance		10,70	Ohm/km

## ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli  
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

PierPaolo Piccinini

**Description**

Double shielded coaxial cable - 75 Ohm

Double shielded cable (Screening Class A+)



Data Sheet

**RP913B**

Loop resistance		28,70	Ohm/km
Sheat Insulation voltage (spark test)		3	kV
Maximum current (Ieff)		8	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>28 dB		
1000 - 2000 MHz	>26 dB		
2000 - 3000 MHz	>22 dB		
Screening Attenuation (SA)	SA-Class A++	Shield Transfer Impedance (Zt)	Zt-Class A+
30 - 1000 MHz	>110 dB	5 - 30 MHz	< 2,5 mOhm/m
1000 - 2000 MHz	>105 dB		
2000 - 3000 MHz	>90 dB		


Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,40	862	17,30
10	1,90	1000	18,70
30	3,00	1750	25,70
50	4,00	2150	28,80
200	8,10	2400	30,60
300	9,90	3000	34,10
470	12,60		

Attenuazione di schermatura / Screening Attenuation

**Cavo classe A++ / A++ Class cable**

Cavo tipo / Cable type: RP913B



**ITALIANA CONDUTTORI s.r.l.**

Viale Zanotti 90 I - 27027 Gropello Cairoli  
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

PierPaolo Piccinini

**Description**

Double shielded coaxial cable - 75 Ohm

Double shielded cable (Screening Class A+)

**Data Sheet****RP913B****Connectors**

<b>BNCC703</b>	Series BNC Compression, BNC Compression, for OUTDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm
<b>F703</b>	Series F Crimp, F Crimp, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
<b>FA703</b>	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
<b>FC7.0QM</b>	Series F Compression, Quick Mount, for OUTDOOR installation
<b>FC703</b>	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass - 30,0 mm x 12,0 mm
<b>FCEM7.0C</b>	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass
<b>FCPO5.1C</b>	Series F Compression, Ø 5,1 Push-On, for OUTDOOR installation, nitin-plated brass
<b>IECF5.1C</b>	Series IEC (toolless), female, no tool, for INDOOR installation
<b>IECF90C</b>	Series IEC (toolless), Ø 5,1 90° female, for INDOOR installation
<b>IECF703</b>	Series IEC Compression, female, no tool, for OUTDOOR installation
<b>IECM5.1C</b>	Series IEC (toolless), male, no tool, for INDOOR installation
<b>IECM90C</b>	Series IEC (toolless), Ø 5,1 90° male, for INDOOR installation
<b>IECM703</b>	Series IEC Compression, male, for OUTDOOR installation
<b>FC703C</b>	Series F Compression, F Compression, for OUTDOOR installation
<b>BNCC5.1C</b>	Series BNC Compression, BNC Compression, for OUTDOOR installation

**ITALIANA CONDUTTORI s.r.l.**

Viale Zanotti 90 I - 27027 Gropello Cairoli  
 Tel +39-382.815150 Fax +39-0382.814212

**Date****29/02/2016****Responsible****PierPaolo Piccinini**