

Description


Local Area Network Cable

Cat. 6 U/UTP 4x2xAWG23/1 PVC



Data Sheet

LAN640



Ø	0,57	1,00	6,60
	(Cu)	(PE)	(PVC)

Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EIA-TIA 568-B-2	ISO/IEC 11801 2° ed.	IEC 61156-5	EN 50173
EN 50288-6-1			

Reaction to Fire

IEC 60332-1	EN50575
-------------	---------

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)
 IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T
 IEEE 802.5 16 MB: ISDN; TPDDI; ATM
 Power over Ethernet (PoE)/PoE+

Construction data

4 pairs with conductor of bare copper wires	(Cu)	Ø 0,57	mm
Insulation of solid Polyethylene	(PE)	Ø 1,00	mm

Composition

Twisted pairs, coloured by Standard TIA-568A

Cross separator in Polyethylene	(PE)	Ø 4,00	mm
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 6,60	mm

Printed each meter by blue ink-jet :

**CAVEL LAN640 MADE IN ITALY CAT 6 U/UTP 4x2xAWG23 Euroclass Eca ISO-IEC 11801 EN50173
 CEI-UNEL 36762 C-4 (U0 = 400V) gggaan m**

(ggg=day)(aa=year)(n=batch) (m=meter marking)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date

29/05/2017

Responsible

Giuseppe Guastella

Description

Local Area Network Cable

Cat. 6 U/UTP 4x2xAWG23/1 PVC



Data Sheet

LAN640

Physical data

Weight of copper conductors	18,56	kg/km
Total weight of cable	45,20	kg/km
Minimum bending radius x1/n	35/70	mm
Maximum cable pulling strength	100	N
Maximum tensile strength during the installation	100	N
Installation temperature	0 / +50	°C
Operating temperature	-20 / +60	°C

Electrical data

Characteristic impedance	100 MHz	100 ± 5	Ohm
	100 - 250 MHz	100 ± 22	Ohm
Capacitance of Twisted Pair (@800Hz)		48	pF/m
Velocity Ratio		67 %	
DC Conductor Resistance		80	Ohm/km
Loop resistance		160	Ohm/km
Insulation resistance		5000	MOhm/km
Sheath Insulation Voltage (DC, 1 min)		1	kV
Coupling Attenuation		> 45	dB

Transmission-Characteristic (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	SRL [dB]	NEXT [dB]	ACR [dB]	FEXT [dB]
1	1,80	25,00	100,00	98,20	90,00
10	5,40	25,00	80,00	74,60	70,00
20	7,70	25,00	70,00	62,30	60,00
31,2	9,60	25,00	65,00	55,40	53,00
62,5	13,70	25,00	60,00	46,30	50,00
100	17,40	25,00	60,00	42,60	48,00
155,5	21,90	25,00	55,00	33,10	46,00
200	25,00	20,00	55,00	30,00	44,00
250	28,10	20,00	50,00	21,90	40,00
300	30,80	20,00	45,00	14,20	

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

29/05/2017

Responsible

Giuseppe Guastella