

# HSX5 SERIES

- ▶ Adjustable output level 0... -12dB
- ▶ High cross-polar isolation
- ▶ SAT/Terrestrial TV isolation
- ▶ LNB powered by receiver

Ready for  
**UHDTV** WARRANTY **5** YEARS

ITEM CODE	HSX54	HSX54-20
TYPE	Cascadable	
NUMBER OF IN/OUT	5/5	
NUMBER OF TAPS	4	4
FREQUENCY BAND IF-SAT	MHz	950... 2200
IF-SAT INPUT LEVEL MAX.	dB $\mu$ V*	90
THROUGH LOSS IF-SAT	dB	< 1,5
TAP GAIN	dB	0... -12 (Adjustable)
CROSS-POLAR ISOLATION	dB	> 35
ISOLATION INPUTS/OUTPUTS	dB	> 30
RETURN PATH LOSS (5...100 MHz)	dB	-16
TV TAP LOSS	dB	-16
THROUGH LOSS TV	dB	≤ 2
SAT/TERR. TV SEPARATION	dB	> 50
RETURN LOSS	dB	≥ 12 dB
USER CONSUMPTION MAX.	mA	60
LNB CONSUMPTION MAX	mA	300
DIMENSIONS	88x110x35h	



ITEM CODE	HSX58	HSX58-20
TYPE	Cascadable	
NUMBER OF IN/OUT	5/5	
NUMBER OF TAPS	8	8
FREQUENCY BAND IF-SAT	MHz	950... 2200
IF-SAT INPUT LEVEL MAX.	dB $\mu$ V*	90
THROUGH LOSS IF-SAT	dB	< 3
TAP GAIN	dB	0... -12 (Adjustable)
CROSS-POLAR ISOLATION	dB	> 35
ISOLATION INPUTS/OUTPUTS	dB	> 30
RETURN PATH LOSS (5...100 MHz)	dB	-20
TV TAP LOSS	dB	-20
THROUGH LOSS TV	dB	≤ 4
SAT/TERR. TV SEPARATION	dB	> 50
RETURN LOSS	dB	≥ 12 dB
USER CONSUMPTION MAX.	mA	60
LNB CONSUMPTION MAX	mA	300
DIMENSIONS	88x172x35	



