

WISI DRP 1533

Wall wart 230 V AC, 15 V DC



Description

The DRP 1533 is a wall wart with 230 V AC, 50/60 Hz and has a output power from 15 V DC. It is usable for the FLEXSWITCH series.

At a glance:

- Operating voltage 230 V AC
- Output power 15 V DC
- Output current 3,3 A

Technical data

General data

Connector	Connector type DC 5.5/2.1 mm
Input voltage	100..240 V AC (50/60 Hz)
Operating range	90...264 V AC (50/60 Hz)
Output voltage	15 V DC
Max. output current	3,3 A
Max. output power	49,5 W
Average operational efficiency	87,8 %
Low load efficiency (10%)	80,6 %
Max. humidity, non condensing	75 %
Protection class	II
Protection class system EN 60529 (DIN 40050)	IP40
Electrical safety standard	EN 60950-1
EMC	EN 50083-2
Dimensions W x H x D	116 x 33 x 51 mm
Operating temperature range	-20...+40 °C
Storage temperature	-10...+80 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	170 x 130 x 52 mm
Packaging volume sales unit	1,1 dm ³
Gross weight sales unit	0.44 kg
Shipping unit	1 pcs.
Dimensions (WxHxD) shipping unit	170 x 130 x 50 mm
Packaging volume shipping package	1,1 dm ³
Gross weight shipping unit	0,44 kg
EAN	4010056749835
Article number	74983
Customs tariff number	85044090