


GDM 10 3-way MM Wall Outlet

Art. Number 306272



GDM 10 3-way MM Wall Outlet

- Frequency range of 5...1200/1800 MHz for all levels of DOCSIS 3.1 migration - still compatible with existing standards
- Available in single (EDM) and loopthrough (GDM) models
- Superb electrical performance
- High screening attenuation Class A+10dB.
- Quick and easy mounting "push-lock" mechanism
- Approved by Vodafone - Kabel Deutschland

Technical Specifications

ORDER INFORMATION

EAN Number 5702663062726

SHIELDING

Shielding @ 1000...1794 MHz dB	≥ 85.0 dB
Shielding @ 1794...3000 MHz dB	≥ 65.0 dB
Shielding @ 470-1000 MHz dB	≥ 85.0 dB
Shielding @ 5...470 MHz dB	≥ 95.0 dB

CHARACTERISTICS

Outlet Type Loop through

FREQUENCY RANGE

Frequency Range DATA MHz	5...1794 MHz
Frequency Range DATA - RP MHz	5...65...85 MHz
Frequency Range IN-OUT MHz	5...1794 MHz
Frequency Range RF MHz	87.5...108 MHz
Frequency Range TV MHz	109...1218 MHz

LOSS

Through Loss IN-DATA 1218...1794MHz | dB 11.2 dB



Technical Specifications

Through Loss IN-DATA 5...1218MHz dB	10.2 dB
Through Loss IN-OUT 1000...1218 MHz dB	3.8 dB
Through Loss IN-OUT 1218...1794 MHz dB	4.8 dB
Through Loss IN-OUT 5...1218 MHz dB	3.6 dB
Through Loss IN-RF 5...65MHz dB	52.0 dB
Through Loss IN-RF 87.5...108MHz dB	12.5 dB
Through Loss IN-TV 1000...1218 MHz dB	10.0 dB
Through Loss IN-TV 109...1000MHz dB	10.0 dB
Through Loss IN-TV 5...65MHz dB	52.0 dB

ISOLATION

Isolation DATA/TV/R 200...862MHz dB	30.0 dB
Isolation DATA/TV/R 5...65MHz dB	60.0 dB
Isolation DATA/TV/R 85...200MHz dB	40.0 dB
Isolation DATA/TV/R 862...1218MHz dB	20.0 dB
Isolation OUT/DATA 1218...1794MHz dB	18.0 dB
Isolation OUT/DATA 200...1218MHz dB	20.0 dB
Isolation OUT/DATA 5...200MHz dB	20.0 dB
Isolation OUT/TV/R 5...65MHz dB	60.0 dB
Isolation OUT/TV/R 65...862MHz dB	25.0 dB
Isolation OUT/TV 862...1218MHz dB	20.0 dB
Isolation OUT/TV/R dB	30.0 dB
Isolation TV-RF dB	20.0 dB

RETURN LOSS

Return Loss DATA dB	18.0 -1.5/oct dB
Return Loss IN/OUT dB	18.0 -1.5/oct dB
Return Loss IN/OUT/DATA 1218...1794MHz dB	8.0 (@1794MHz) dB
Return Loss RF dB	10.0 dB
Return Loss TV dB	14.0 -1.5/oct dB

ELECTRICAL

Impedance Ω	75 Ω
----------------------	-------------

OPERATIONAL

Screening Efficiency	EN50083-2 (Class A+10dB)
----------------------	--------------------------

CONNECTORS

Connector DATA	F-female (IEC 61)
Connector IN-OUT	Spring Clamp Termination
Connector RF	IEC-female
Connector TV	IEC-male

MECHANICAL

Packaging Depth m	0.040 m
---------------------	---------



Technical Specifications

Packaging Height m	0.070 m
Total Weight kg	0.114 kg
Packaging Width m	0.070 m
Net Weight kg	0.104 kg
Packing QTY	10
Remarks	For interactive multimedia CATV
Tara Weight kg	0.010 kg
Packaging Volume m3	0.000 m3