

Description

Outdoor drop coaxial cable - 75 Ohm
Outdoor installation cable (Screening Class A)

Coaxial Cables

CAVEL®

since 1968

Data Sheet

11/48LO



Ø	1,13	4,80	4,90	5,30	7,30
	(Cu)	(PEG)	(Cu/Pet)	(Cu)	(PE)

Class CPR acc. to UE 305/2011 (DoP)

Fca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EN 50117-2-5

Reaction to Fire

EN50575

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,13 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,80 ± 0,10	mm
Copper/Polyester tape longitudinally overlapped	(Cu/Pet)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of annealed copper wires	(Cu)		
Braid optical coverage (IEC 96-1)		59	%
Tracer Identifier	Year + Flag		
Diameter over Braid		Ø 5,30	mm
Outer sheath of Polyethylene - black - with carbonblack	(PE)	Ø 7,30 ± 0,10	mm

Printed each meter by yellow ink-jet :

CAVEL 1.1/4.8 LO MADE IN ITALY 75 Ohm Euroclass Fca EN50117-2-5 CEI-UNEL 36762 C-4 (U0 = 400V)
gggaan m

(ggg=day)(aa=year)(n=batch) (m=meter marking)

Physical data

Weight of copper conductors	20,50	kg/km
Total weight of cable	48,00	kg/km
Minimum bending radius (single/repetead bending)	50	mm
Maximum cable pulling strength	200	N
Minimum installation temperature	-5	°C
Operating temperature	-40 / +80	°C

Electrical data

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		18	Ohm/km
Outer conductor resistance		14,80	Ohm/km
Loop resistance		32,80	Ohm/km

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

11/05/2017

Responsible

Alberto Scardovi

Description

Outdoor drop coaxial cable - 75 Ohm
 Outdoor installation cable (Screening Class A)



Data Sheet


11/48LO

Sheat Insulation voltage (spark test)	8	kV
Maximum current (Ieff)	8	A
Structural return loss (SRL)		
5 - 470 MHz	>30 dB	
470 - 1000 MHz	>28dB	
1000 - 2000 MHz	>26 dB	
2000 - 3000 MHz	>22 dB	
Screening Attenuation (SA)	SA-Class A	Transfer Impedance (Zt)
30 - 1000 MHz	> 85 dB	5 - 30 MHz
1000 - 2000 MHz	> 90 dB	
2000 - 3000 MHz	> 75 dB	Zt-Class A
		< 11,0 mΩ/m

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,50	862	16,80
10	2,10	1000	17,90
30	2,90	1750	24,80
50	3,80	2150	27,30
200	7,90	2400	29,10
300	9,70	3000	33,00
470	12,00		

Attenuazione di schermatura / Screening Attenuation
Cavo classe A / A Class Cable
 Cavo tipo / Cable type: 11/48LO (new version)



ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date

11/05/2017

Responsible

Alberto Scardovi