

## Taps 5-2400 MHz

- excellent amplitude frequency response
- high screening factor >100 dB by fully soldered housing
- EMI decoupled by capacitive separators
- plastic bracket for wall mounting included
- long hole fastener
- ground clamp 4 mm<sup>2</sup>



Technische Daten / Technical data								
Typ / Type	FAS 1-10	FAS 1-16	FAS 2-10	FAS 2-16	FAS 4-10	FAS 4-16	FAS 6-16	FAS 8-16
Artikel-Nr. / Article no.	3262000	3262100	3262300	3262400	3262510	3262520	3262530	3262540
Abzweiger / Tap	1	1	2	2	4	4	6	8
Durchgangsdämpfung (IN-OUT) 5-862 MHz	1,8 dB	1,3 dB	3,2 dB	2,4 dB	4,5 dB	2,8 dB	3,6 dB	4,8 dB
Through loss (IN-OUT) 950-2400 MHz	2,8 dB	1,8 dB	4,2 dB	3,2 dB	5,5 dB	4,8 dB	6,5 dB	6,5 dB
Abzweigdämpfung (IN-TAP) 5-862 MHz	10 dB	15 dB	10,5 dB	15 dB	11,5 dB	15 dB	16 dB	16 dB
Tap loss (IN-TAP) 950-2400 MHz	10,5 dB	15 dB	11 dB	15,5 dB	13,5 dB	16 dB	19 dB	19 dB
Entkopplung (TAP-TAP) 5-862 MHz	/	/	32 dB	36 dB	21 dB	22 dB	22 dB	22 dB
Isolation (TAP-TAP) 950-2400 MHz	/	/	20 dB	26 dB	18 dB	20 dB	16 dB	16 dB
Entkopplung (OUT-TAP) 5-862 MHz	25 dB	26 dB	21 dB	23 dB	23 dB	25 dB	23 dB	23 dB
Isolation (OUT-TAP) 950-2400 MHz	23 dB	23 dB	16 dB	18 dB	18 dB	20 dB	21 dB	21 dB
Rückflussdämpfung (IN/OUT/TAP) 5-862 MHz	13 dB	13 dB	12 dB	12 dB	9 dB	12 dB	10 dB	10 dB
Return loss (IN/OUT/TAP) 950-2400 MHz	10 dB	10 dB	12 dB	12 dB	10 dB	12 dB	8 dB	8 dB