

# WISI DD 04 M 0650

Broadband modem sockets, stub sockets, F



## Description

TV connection with IEC technology. Multimedia with F-connector or WICLIC for cable modem. HF output high-pass filtered. Cover plate and connector cable see accessories

## At a glance:

- Approved by Vodafone Kabel Deutschland
- Very high decoupling of DATA/TV/Radio connections
- Screwable inner conductor clamp for secure and durable connection

Technical data	
<b>Inputs</b>	
Frequency range	5...1006 MHz
<b>Outputs</b>	
Frequency range TV	85...1006 MHz
Frequency range FM	87...1006 MHz
Frequency range DATA	5...1006 MHz
Rejection loss TV	≥40 dB (5...65 MHz)
Rejection loss FM	≥40 dB (5...65 MHz)
Insertion loss TV	4 dB
Insertion loss FM	8 dB
Insertion loss DATA	8 dB
Isolation DATA - TV	≥70 dB (5...65 MHz)
Isolation DATA - TV	≥35 dB (85...1006 MHz)
Isolation DATA - FM	≥70 dB (5...65 MHz)
Isolation DATA - FM	≥40 dB (85...1006 MHz)
Return loss IN, OUT	≥18 dB (-1.5 dB/oct.)
Return loss TV	≥14 dB (-1.5 dB/oct.)
Return loss FM	≥14 dB (-1.5 dB/oct.)
Return loss DATA	≥18 dB (-1.5 dB/oct.)
Intermodulation ratio	> 120 dB $\mu$ V (EN60728-4)
<b>Connectors</b>	
Outer conductor clamp	7,5 mm
Inner conductor clamp	0,6...1,3 mm
F-female	1 pcs. EN60169-24
IEC socket	1 pcs. EN60169-2
IEC-plug	1 pcs. EN60169-2
<b>General data</b>	
Screening factor	>85 dB Class A, EN 50083-2
Dimensions (width x height x depth)	70 x 70 x 22 mm
Installation depth	35 mm

Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	212 x 148 x 78 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.11 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.22 dm <sup>3</sup>
Gross weight shipping unit	0.11 kg
EAN	4010056145668
Article number	14566
Customs tariff number	85291095