

Crimping Tools



BTC Series

BT & RJ Connector Crimper



- Combination tool integrates a crimper, wire cutter & jack stripper into one tool body
- Compatible with British Telecom 630A/631A modular connectors & RJ11, RJ12 & RJ45 connectors
- Ratchet mechanism easily releases even during mid-cycle operations

MODEL	PART #	BLADE PART #	LENGTH	WEIGHT
BTC	40000	80757 (Set of 2)	7.75" (197 mm)	12 oz (340 g)



RJC Series

RJ Connector Crimper



- Combination tool integrates a crimper, wire cutter & jack stripper into one tool body
- Compatible with RJ22 & RJ45 modular RJ connectors (4P, 6P, 8P)
- Ratchet mechanism easily releases even during mid-cycle operations

MODEL	PART #	BLADE PART #	LENGTH	WEIGHT
RJC	80756	80757 (Set of 2)	7.75" (197 mm)	12 oz (340 g)



CT Series

LMR® Cable Connector Hex Crimpers



- Premium quality crimping tool for Times Microwave Systems LMR® cables & connectors
- Fixed hex jaws* are precision alloy steel, self-bottoming & will not over-crimp
- Rugged steel frame construction provides maximum strength & ensures tool longevity

MODEL	PART #	CABLE COMPATIBILITY	CONNECTOR COMPATIBILITY	LENGTH	WEIGHT
CT300/400	42465	LMR300	Crimp Style	9" (229 mm)	1 lb 9 oz (708 g)
		LMR400			
CT240/200/100	42650	LMR240	Crimp Style		
		LMR200			
		LMR100			

*Jaws cannot be replaced



CR Series

CATV, MATV & STV Cable Connector Hex Crimper



- Hex crimping tool for CATV, MATV & STV connectors with precision, self-bottoming alloy steel jaws
- Toggle action delivers correct crimping force & star wheel allows for compression adjustment
- Rugged steel frame with heat-treated pins for maximum durability & longevity

MODEL	PART #	HEX SIZE	CONTACT HEX	LENGTH	WEIGHT
CR 211CX	33315	0.475" (12.07 mm)	0.096" (2.43 mm)	9" (229 mm)	1 lb 9 oz (708 g)
CR 270/213	35463	0.270" / 0.213" (6.85 / 5.41 mm)	N/A		
CR 596B	33320	0.324" / 0.262" (8.23 / 6.65 mm)	N/A		
CR 596QL	33335	0.360" / 0.324" (9.14 / 8.23 mm)	N/A		
CR 41Q	33275	0.453" / 0.315" (11.15 / 8.00 mm)	N/A		
CR 611QL	34475	0.470" / 0.324" (11.94 / 8.23 mm)	N/A		
CR 470/410	35460	0.470" / 0.410" (11.94 / 10.41 mm)	N/A		
CR 611Q2	34485	0.475" / 0.324" (12.07 / 8.23 mm)	0.100" (2.54 mm)		
CR 611U	34930	0.475" / 0.360" (12.07 / 9.14 mm)	0.096" (2.43 mm)		