

WISI VX 82 2P

In-house amplifier



Description

At a glance:

- Zinc die-cast housing
- Flap-lid for easy handling
- Screening ensured with open flap-lid
- Configuration of attenuators and equalizers via PADS and jumpers
- Measuring point at the output
- Return path amplifier on the circuit board
- Low power consumption, high output level
- Unitymedia certified

Technical data

Downstream

Inputs	1 pcs.
Frequency range downstream	85...1006 MHz
Gain downstream	33 dB
Noise figure downstream	≤6,0 dB
attenuator downstream	0...20 dB
equaliser downstream	0...20 dB (Interstage-equalizer 0/7 dB)
Output level 1	99 dB μ V (CENELEC 42 channels, flat, at CSO/CTB >60 dB/>60 dB)

Upstream

Frequency range upstream	5...65 MHz
Gain upstream	23 dB
noise figure upstream	≤5 dB
attenuator upstream input	0...20 dB
Equalizer US	3 dB (Interstage, fix)
Output level 4	120 dB μ V (KDG 1TS140 - average load with QAM 64 MER >35 dB, BER 1x10 ⁻⁸)
Output test point	-20 dB

Connectors

F-socket	3 pcs.
----------	--------

General data

Operating voltage AC	230 V (50/60 Hz)
Power consumption	≤6,0 W
EMC	EN 50083-2
Dimensions (width x height x depth)	163x90x50 mm
Operating temperature range	-20...+55 °C
Protection class	IP20
Lightning protection	1 kV (EN60728-3, 1,2/50 μ s pulse)

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	166 x 143 x 50 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.810 kg
Shipping unit	1 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	kg
EAN	4010056720858
Article number	72085
Customs tariff number	85437030